

Dominion Diamond Corporation

Jay Project Developer's
Assessment Report

Hydrology



Overview

Overview of Assessment and Key Concepts

- General overview of presentation
 - Introduction
 - Jay Project DAR sections for the Hydrology Discipline
 - Assessment approach for the Hydrology discipline
 - Existing Environment
 - Methods
 - Results
 - Assessment
 - Methods
 - Results
 - Summary



Introduction

Water Quality and Quantity Components found in the Jay Project DAR

Section/ Appendix Number	Section Title
Section 8	Key Line of Inquiry: Water Quality and Quantity
Appendix 8A	Hydrogeological Model for Pre-Mining, Mining, and Closure
Appendix 8B	Hydrogeological Model for Jay Pit - Post Closure
Appendix 8C	Hydrogeological Model for Misery Pit – Post Closure
Appendix 8D	Regional Water Balance Model
Appendix 8E	Site Discharge Water Quality Modelling
Appendix 8F	Hydrodynamic Models of Lac du Sauvage and Lac de Gras
Appendix 8G	Hydrodynamic Model of Jay and Misery Pits
Appendix 8H	Acute Toxicity Testing of Predicted Jay Effluent

Introduction

Water Quality and Quantity Components found in the Jay Project DAR - continued

Section/ Appendix Number	Section Title
Annex III	Geology Baseline
Annex VIII	Geochemistry Baseline
Annex IX	Hydrogeology Baseline
Annex X	Hydrology Baseline
Annex XI	Water and Sediment Quality Baseline

Assessment Approach

Valued Components, Assessment Endpoints and Measurement Indicators


Valued Component	Assessment Endpoint	Measurement Indicator
Groundwater	<ul style="list-style-type: none"> No specific assessment endpoint Changes to groundwater are carried forward into the effects analysis for surface water quantity and quality 	<ul style="list-style-type: none"> Groundwater levels and flow rates Spatial and temporal distribution of groundwater Concentrations of physical analytes (e.g., pH, conductivity) Concentrations of major ions and nutrients Concentrations of total and dissolved metals
Surface Hydrology	<ul style="list-style-type: none"> No specific assessment endpoint Changes to drainage paths, water levels, and discharges are carried forward into the effects analysis for surface water quality, fish and fish habitat, and traditional land use 	<ul style="list-style-type: none"> Lake water levels and outflow discharge rates Stream channel parameters (e.g., channel depths, widths) and shoreline integrity Basin water yields
Water Quality	<ul style="list-style-type: none"> Maintenance or suitability of surface water quality for healthy and sustainable aquatic and terrestrial ecosystems Ecological function is maintained Aquatic life is not impaired 	<ul style="list-style-type: none"> Concentrations of water and sediment quality constituents: <ul style="list-style-type: none"> In situ physico-chemical water quality parameters (e.g., temperature, dissolved oxygen, pH, conductivity) Major ions, suspended solids, nutrients, and metals in water Distribution of particle size in surficial sediment Nutrients and metals in sediment



Assessment Approach

Baseline Study Area – Hydrology


- The Baseline Study Area included the entire Lac du Sauvage and Lac de Gras watersheds, as well as the Coppermine River downstream to its mouth
- Baseline studies focused on long-term data available for the Lac de Gras watershed and Coppermine River, with field studies focused mainly on the Lac du Sauvage watershed



Assessment Approach

Effects Study Area – Hydrology

- The Effects Study Area includes waterbodies potentially directly affected by the Project
- These include Lac du Sauvage, Lac de Gras, affected tributaries, and Coppermine River to the Desteffany Lake outlet




Assessment Approach

Assessment Cases

Base Case		Application Case	Reasonably Foreseeable Development Case
Reference Condition	2014 Baseline Conditions		
No or minimal human development	Conditions from all previous, existing, and approved developments before the Project	Base Case plus the Project	Application Case plus reasonably foreseeable developments



Existing Environment – Methods: Long-Term Climate Stations



Existing Environment – Methods: Long-term Hydrometric Stations



LEGEND

- Ekati Mine Footprint
- Diavik Mine Footprint
- Proposed Jay Footprint
- Winter Road
- Tibbitt to Contwoyto Winter Road
- Northern Portion of Tibbitt to Contwoyto Winter Road
- Watercourse
- Waterbody
- Hydrology Survey Site
- Hydrometric Station
- Ekati/Diavik Local Meteorological Station
- Local Historical Hydrometric Station

5 0 5
SCALE 1:300,000 KM

Paul Lake and Paul Creek

Ekati Mine

Fox Operation

Existing Misery Road

Misery Operation

Lynx

Diavik Mine

Lake E10 (Ursula Lake)

Lake E12

Lake E409

Lake E391

Lake E387

Lake E2

Lake E38

Lake E1

Lake G17

Lake G13

Lake G6

Lake G5

Lake G4

Lake G474

Lake G2

Lake G1

Lake G521

Lake 118

Lake 12

Lake 11A

Lake 11

Lake 176

Lake 177

Lake 100

Lake 12B

Lake 103

Lake 13 (Starlet Lake)

Lake 10

Lake 11

Lake 12

Lake 13

Lake 14

Lake 15

Lake 16

Lake 17

Lake 18

Lake 19

Lake 20

Lake 21

Lake 22

Lake 23

Lake 24

Lake 25

Lake 26

Lake 27

Lake 28

Lake 29

Lake 30

Lake 31

Lake 32

Lake 33

Lake 34

Lake 35

Lake 36

Lake 37

Lake 38

Lake 39

Lake 40

Lake 41

Lake 42

Lake 43

Lake 44

Lake 45

Lake 46

Lake 47

Lake 48

Lake 49

Lake 50

Lake 51

Lake 52

Lake 53

Lake 54

Lake 55

Lake 56

Lake 57

Lake 58

Lake 59

Lake 60

Lake 61

Lake 62

Lake 63

Lake 64

Lake 65

Lake 66

Lake 67

Lake 68

Lake 69

Lake 70

Lake 71

Lake 72

Lake 73

Lake 74

Lake 75

Lake 76

Lake 77

Lake 78

Lake 79

Lake 80

Lake 81

Lake 82

Lake 83

Lake 84

Lake 85

Lake 86

Lake 87

Lake 88

Lake 89

Lake 90

Lake 91

Lake 92

Lake 93

Lake 94

Lake 95

Lake 96

Lake 97

Lake 98

Lake 99

Lake 100

Lake 101

Lake 102

Lake 103

Lake 104

Lake 105

Lake 106

Lake 107

Lake 108

Lake 109

Lake 110

Lake 111

Lake 112

Lake 113

Lake 114

Lake 115

Lake 116

Lake 117

Lake 118

Lake 119

Lake 120

Lake 121

Lake 122

Lake 123

Lake 124

Lake 125

Lake 126

Lake 127

Lake 128

Lake 129

Lake 130

Lake 131

Lake 132

Lake 133

Lake 134

Lake 135

Lake 136

Lake 137

Lake 138

Lake 139

Lake 140

Lake 141

Lake 142

Lake 143

Lake 144

Lake 145

Lake 146

Lake 147

Lake 148

Lake 149

Lake 150

Lake 151

Lake 152

Lake 153

Lake 154

Lake 155

Lake 156

Lake 157

Lake 158

Lake 159

Lake 160

Lake 161

Lake 162

Lake 163

Lake 164

Lake 165

Lake 166

Lake 167

Lake 168

Lake 169

Lake 170

Lake 171

Lake 172

Lake 173

Lake 174

Lake 175

Lake 176

Lake 177

Lake 178

Lake 179

Lake 180

Lake 181

Lake 182

Lake 183

Lake 184

Lake 185

Lake 186

Lake 187

Lake 188

Lake 189

Lake 190

Lake 191

Lake 192

Lake 193

Lake 194

Lake 195

Lake 196

Lake 197

Lake 198

Lake 199

Lake 200

Lake 201

Lake 202

Lake 203

Lake 204

Lake 205

Lake 206

Lake 207

Lake 208

Lake 209

Lake 210

Lake 211

Lake 212

Lake 213

Lake 214

Lake 215

Lake 216

Lake 217

Lake 218

Lake 219

Lake 220

Lake 221

Lake 222

Lake 223

Lake 224

Lake 225

Lake 226

Lake 227

Lake 228

Lake 229

Lake 230

Lake 231

Lake 232

Lake 233

Lake 234

Lake 235

Lake 236

Lake 237

Lake 238

Lake 239

Lake 240

Lake 241

Lake 242

Lake 243

Lake 244

Lake 245

Lake 246

Lake 247

Lake 248

Lake 249

Lake 250

Lake 251

Lake 252

Lake 253

Lake 254

Lake 255

Lake 256

Lake 257

Lake 258

Lake 259

Lake 260

Lake 261

Lake 262

Lake 263

Lake 264

Lake 265

Lake 266

Lake 267

Lake 268

Lake 269

Lake 270

Lake 271

Lake 272

Lake 273

Lake 274

Lake 275

Lake 276

Lake 277

Lake 278

Lake 279

Lake 280

Lake 281

Lake 282

Lake 283

Lake 284

Lake 285

Lake 286

Lake 287

Lake 288

Lake 289

Lake 290

Lake 291

Lake 292

Lake 293

Lake 294

Lake 295

Lake 296

Lake 297

Lake 298

Lake 299

Lake 300

Lake 301

Lake 302

Lake 303

Lake 304

Lake 305

Lake 306

Lake 307

Lake 308

Lake 309

Lake 310

Lake 311

Lake 312

Lake 313

Lake 314

Lake 315

Lake 316

Lake 317

Lake 318

Lake 319

Lake 320

Lake 321

Lake 322

Lake 323

Lake 324

Lake 325


Lake 326

Lake 327

Existing Environment – Methods: Modeling

Lac du Sauvage Water Balance Model


Figure F3-1 Schematic of Typical Lake Reservoir Model



RC = rainfall runoff coefficient; SC = snowfall runoff coefficient

Existing Environment – Results: Lac du Sauvage and Lac de Gras

	Lac du Sauvage	Lac de Gras
Watershed Area (km ²)	1,461	4,130
Surface Area (km ²)	86	572
Volume (Mm ³)	631	6,155
Maximum Depth (m)	40	50
2-year Flood (m ³ /s)	17.5	28.1
100-year Flood (m ³ /s)	39.6	48.7




Existing Environment – Results: Lac du Sauvage and Lac de Gras



Lac du Sauvage Outlet, May 2014

Existing Environment – Results: Coppermine River



Above Bloody Falls	Above Copper Creek	Point Lake Outlet	Below Desteffany Lake	Lac de Gras	Lac du Sauvage	
50,700	46,200	19,200	6,116	4,130	1,461	Watershed Area (km ²)
	184	178	149	149	149	Mean Water Yield (mm)
	1,430	231	102	28.1	17.5	2-year Flood (m ³ /s)
	3,460	641	351	48.7	39.6	100-year Flood (m ³ /s)

Existing Environment - Results

Hydrology – Traditional Knowledge

- From the available TK information:
 - Local waters have traditionally been used for transportation, drinking, hunting, fishing, trapping, and cleaning and preparing hides and other materials. Open water allows transportation by canoes and other watercraft, and waterbodies provide landmarks for navigation and geographic boundaries.
 - The Lac du Sauvage Narrows has been identified as a particularly important location for camping, hunting, and fishing. The channel has been noted as deep enough to provide for winter movement of fish, and swift currents may keep waters open in the winter, facilitating fishing and easy access to fresh water.
 - Concerns about traditional land use include sensitivities to changes in water levels, which may affect traditional use and wildlife. A periodic lowering of the water levels in the Project area has also been reported, and suggested to potentially affect the direction of surface water flow from the area.
- Traditional Knowledge is generally consistent with the scientific knowledge.

Assessment – Project Activity Screening

Water Quantity (Hydrology)

- Identification of Project activities with a link to potential effects to water quantity



- Screening to identify the magnitude of the linkage: no linkage, secondary (negligible residual effect), primary (likely to result in change)
- Identification of potential overlapping effects between the Project and existing developments to water quantity
 - Cumulative effects

Assessment – Key Mitigations

Water Quantity (Hydrology)

- Roads and culverts will be constructed to limit disturbance and maintain natural drainage patterns
- Dike will be constructed to limit seepage from Lac du Sauvage into the diked area
- Diversion channels will be used to reduce runoff into the diked area
- A detailed dewatering plan will be used to manage discharges from the diked area during dewatering, to prevent harm to Lac du Sauvage, the Narrows, and downstream waterbodies
- A mine water management plan will minimize effects on natural waterbodies, by limiting water withdrawals and recycling process water
- Back-flooding of the Jay Pit and diked area will be managed to prevent harm to Lac du Sauvage, the Narrows, and downstream waterbodies
- Closure activities will reconnect the diked area and restore drainage in diverted basins

Assessment – Pathways Analysis of Water Quantity (Surface Hydrology)

The water quantity assessment focused on changes to water levels, flows and channel/bank stability, and considered Project effects on groundwater as required by the TOR

Pathways were identified and screened:

- 2 No Linkage pathways were identified
 - 6 Secondary pathways were identified
 - 8 Primary pathways were identified and assessed
-
- Altered site drainage and runoff from mine facilities
 - Displacement of water in Lac du Sauvage due to placement of dike material
 - Dewatering of the diked area in Lac du Sauvage
 - Dewatering affecting groundwater and thereby affecting nearby lakes
 - Groundwater seepage from Misery Pit affecting Lac de Gras
 - Operational discharges from Misery Pit to Lac du Sauvage
 - Pumping water from Lac du Sauvage to back-flood the Jay Pit and dewatered dike area
 - Reconnection of the Lac du Sauvage diked area

Assessment Methods – Hydrology

Water Quantity (Hydrology)


- The baseline water balance model was modified to account for changes due to the Project, including:
 - Changes to runoff coefficients due to surface infrastructure and waste rock storage areas
 - Changes to drainage pathways due to surface infrastructure and drainage diversions
 - Changes to waterbody characteristics due to dike construction / breaching
 - Water transfers associated with dewatering, back-flooding, and other water management activities
- The water balance model was run to characterize changes in flows and water levels at key nodes for a range of metrics incorporating natural variability
- Where required (e.g., at the Lac du Sauvage Narrows), flow depths and top widths were also modelled
- Potential for effects on lake and channel bed and bank stability was evaluated qualitatively

Assessment – Water Quantity Boundaries

Water Quantity - Temporal Assessment Boundaries

- Model snapshots, or temporal boundaries for the water balance model outputs:
 - Base Case
 - Existing Conditions (2010 to 2015)
 - Application Case
 - Construction Phase (2016 to 2019)
 - Early Operations Phase (2019 to 2024)
 - Late Operations Phase (2024 to 2029)
 - Closure Phase (2030 to 2033)
 - Post-closure Period (2034 to 2060)
- Spatial boundaries (assessment nodes) were selected based on locations of Project effects, and are shown with the assessment results

Assessment – Water Quantity Spatial Boundaries



Effects were assessed at nodes representing lake water levels and discharges


Assessment – Effects to Lac du Sauvage Tributaries

Water Quantity (Hydrology) – Effects to Lac du Sauvage Tributaries

Lake	Effects Due To	Water level and discharge changes
Ac35	Project infrastructure, runoff diversion	Discharges increase up to 1% during construction; water levels unchanged
B0	Project infrastructure, WRSA, runoff diversion	Maximum discharge increase 10%; maximum water level increase 0.09 m
C1	WRSA, groundwater losses	Maximum discharge decrease 58%; maximum water level decrease 0.17 m
C17	WRSA	Maximum discharge decrease 80%; maximum water level decrease 0.72 m

- Effects on water levels and discharges at Lakes C1 and C17 were modelled conservatively by assuming WRSA runoff will be diverted
- Lake and channel bank and bed stability will not be affected
- Figures and tables showing Project effects are provided in DAR Section 8.5.3


Assessment – Water Quantity Spatial Boundaries



Effects were assessed at nodes representing lake water levels and discharges

Assessment – Effects to Lac du Sauvage and Lac de Gras


- The greatest increases in Lac du Sauvage (LDS) and Lac de Gras (LDG) water levels are expected to occur during dewatering
- Increases in water levels are expected to be limited to 5 cm (LDS) and 6 cm (LDG)
- Increases in discharges are expected to range from 4% to 10% (LDS) and 4% to 6% (LDG)
- None of these changes are expected to affect lake or channel bank or bed stability



Above: Predicted water level changes at Lac du Sauvage during dewatering

Assessment – Effects to Lac du Sauvage and Lac de Gras


- The greatest decreases in Lac du Sauvage (LDS) and Lac de Gras (LDG) water levels are expected to occur during back-flooding at closure
- Decreases in water levels are expected to be limited to 5 cm (LDS) and 8 cm (LDG)
- Decreases in discharges are expected to range from 5% to 22% (LDS) and 3% to 6% (LDG)
- None of these changes are expected to affect lake or channel bank or bed stability



Above: Predicted water level changes at Lac du Sauvage during back-flooding

Assessment – Effects to Lac du Sauvage Narrows


- The greatest increases in Lac du Sauvage Narrows depths and top widths are expected to occur during dewatering
- Increases in water levels are expected to be limited to 4 cm
- Increases in top widths are expected to be limited to less than 3 m
- None of these changes are expected to affect lake or channel bank or bed stability



Above: Predicted channel depth changes at Lac du Sauvage during dewatering

Assessment – Effects to Lac du Sauvage Narrows

- The greatest decreases in Lac du Sauvage Narrows depths and top widths are expected to occur during back-flooding
- Decreases in water levels are expected to be limited to 5 cm
- Decreases in top widths are expected to be limited to less than 4 m
- None of these changes are expected to affect lake or channel bank or bed stability



Above: Predicted channel depth changes at Lac du Sauvage during back-flooding

Assessment – Conclusion

Water Quantity (Hydrology) - Summary

- Changes to discharges and water levels at key nodes for each Project phase or period were predicted
- Changes to discharge and water levels are generally predicted to be small, except for a few situations at small Lac du Sauvage tributary lakes/streams
- No measureable long-term changes to discharges and water levels are predicted at Lac du Sauvage and Lac de Gras during the Post-Closure period
- Lake and channel bed and bank stability will not be affected by changes to discharges and water levels
- Changes were passed to the water quality, fish and fish habitat and traditional land use disciplines, as inputs to their assessments
- Additional hydrological monitoring in anticipate as an extension of the existing Ekati monitoring programs within the AEMP

Thank You

